

# **GLOSS BOSS**<sup>®</sup>



## ***GB1500 Electric Burnisher***

*The GB1500's unique "free floating" burnishing head adapts to uneven floor surfaces with remarkable efficiency. This creates lower amp draw for operation in buildings with standard power. The "vacuum assisted start-up" controls excessive starting torque and high amp draw as gradual contact is made with floor and RPM's increase. The handle mounted amp meter indicates when pad adjustment is necessary. Operator simply adjusts pressure with conventionally located knob.*

# ***PULLMAN-HOLT***

## **GB1500 Electric Burnisher Features:**

- Heavy-duty slow release 15AMP circuit breaker protects against overload.
- Sealed main wheel bearings are permanently lubricated with steel hubs and positive locking nuts.
- 50 ft. power cord enables operator to cover a large area without changing outlets.
- Semi-pneumatic 6" non-marking rubber main wheels with permanently lubricated ball bearings.
- Permanently welded wheel axles maintain alignment and precision balance improving machine operation.
- Safety latch, thumb operated, prevents accidental start-up.

## **Specifications:**

<b>Coverage:</b>	15,000 Sq. Ft. of floor area per hour.
<b>Motor:</b>	Heavy-duty single phase 1.5 HP, 120V, 60HZ dual capacitor motor provides necessary power for burnishing.
<b>Pad Speed:</b>	1500 RPM, 20" pad diameter UL listed.
<b>Pad Drive System:</b>	Dynamically balanced, cast iron pulley with six groove poly V belt drive and permanently lubricated, self alignment bearings. Pad driver shaft 1" dia.
<b>Pad Drive Block:</b>	1" marine plywood with centering and locking device to accept 20" pads.
<b>Construction:</b>	Chassis - 12 gauge welded steel with corrosive resistant, baked enamel finish. Handle - 1/4" dia. chrome plated, heavy gauge steel pipe. Switch Box - Die cast aluminum with corrosion resistant, baked enamel finish.
<b>Warranty:</b>	Motor 3 years, Parts 1 year
<b>Model:</b>	GB1500F (B524350); Shpg. Wt. 113 lbs., 1 ctn.



# **PULLMAN HOLT**